

Firmware Release Notes

Air Remote TTL-C (for Canon)

AIR REMOTE TTL-C FIRMWARE VERSION: B6

GENERAL NOTES

The Air Remote TTL-C is designed to be “future proof” and the firmware can be upgraded via the USB port. Be sure to not miss important upgrades on your product. Register your Air Remote TTL-C on Profoto.com/register to receive first-hand information of future upgrades on your product.

This release note covers firmware specific information. Detailed functionality descriptions are found in the User Guide.

The Air Remote TTL-C can generally be operated in two optional modes, TTL mode or Manual Mode. When full functionality is stated in this release note it means support for operating in both modes.

- TTL mode – Off-Camera flash TTL control.
- Manual mode – Wireless manual flash control & flash sync.

NEW IN FIRMWARE VERSION B6

Fix solving TTL over-exposure issue with Canon EOS 5DS, 5DSR and 1D C.

Fix allowing faster continuous shooting in manual flash mode. This fix also allows ETTL or Manual flash mode to be selected in camera menu (previously only possible to select on remote).

New feature making it possible to deactivate the auto power off function after 30 minutes of inactivity.

Improved display sleep/dimming function. The display is now partially dimmed after 20 seconds and turns inactive after 2 minutes of inactivity.

Minor bug fixes.

HOW TO CHECK FIRMWARE VERSION

Press and hold the MODE button (upper right) for 10 seconds when the remote is turned on. When “Hello” is shown in display, release finger from button and the firmware version will be displayed.



PROFOTO FLASH COMPATIBILITY

- Full functionality with Profoto AirTTL flashes.
- Full manual mode excluding HSS with Profoto Air flashes.
- Partial manual mode functionality (sync only) with Profoto AirS flashes.

The list of Profoto flashes below lists are all validated with Air Remote TTL-C firmware version **B6**.

PROFOTO FLASH	FULL FUNCTIONALITY INCLUDING TTL AND HSS	MANUAL MODE EXCLUDING HSS	SYNC ONLY NO HSS
B1 500 AirTTL*	✓		
B2 250 AirTTL**	✓		
D1 250 Air		✓	
D1 500 Air		✓	
D1 1000 Air		✓	
D4 1200 Air		✓	
D4 2400 Air		✓	
D4 4800 Air		✓	
Pro-8A 1200 Air		✓	
Pro-8A 2400 Air		✓	
Pro-B4 1000 Air		✓	
Pro-B3 AirS			✓
AcuteB2 600 AirS			✓

* B1 500 AirTTL with firmware upgraded to version C7

** B2 250 AirTTL with firmware upgraded to version A3

Firmware Release Notes

Air Remote TTL-C (for Canon)

AIR REMOTE TTL-C FIRMWARE VERSION: B6

CANON EOS COMPATIBILITY

The list of EOS cameras below lists the camera models that are tested and approved with Air Remote TTL-C with firmware version **B6**. If your EOS camera is not listed but supports E-TTL-II it will most likely still work but it has not yet been confirmed in Profoto tests. Newer cameras released after this firmware update may not work until next firmware update. Canon is not supporting Profoto with gear or protocols and Profoto cannot issue any guarantees that future camera models can be supported.

INTERNATIONAL MODEL NAME	US MODEL NAME	JAPANESE MODEL NAME	AIR REMOTE TTL-C WITH FIRMWARE B6			
			TTL	HSS	1 ST CURTAIN SYNC	2 ND CURTAIN SYNC
1D X			OK	OK	OK	OK
1D C			OK	OK	OK	OK
1Ds MK III			OK	OK	OK	OK
5DS/5DS R			OK	OK	OK	OK
5D MK III			OK	OK	OK	OK
5D MK II			OK	OK	OK	OK
7D MARK II			OK	OK	OK	OK
7D			OK	OK	OK	OK
6D			OK	OK	OK	OK
70D			OK	OK	OK	OK
700D	Rebel T5i	Kiss X7i	OK	OK	OK	OK

Profoto reserves the right to make changes without further notice.